

应用规范 Application NORM

公称压力: 1.6-6.4MPa
 适用温度范围: -40-180°C-280°C
 适用介质: 水、油、气及某些腐蚀性液体(W.O.G)
 螺纹类型: G.NPT.BSPT.BSP.DIN259/2999

Working Pressure: 1000PSI
 Temperature Range: -40-180°C-280°C
 Suitable medium: Water, oil, air and some Corrosive liquid
 Thread type: G. NPT. BSPT. BSP. DIN259/2999

零件及材质表 Table of parts and materials

零件 Part	材质 Material
阀体 Body	CF8M/CF8
阀盖 Bonnet	CF8M/CF8
球 Ball	CF8M/CF8
阀杆 Stem	SUS316/304
球垫 Ball gasket	PTFE
把手 Handle	SUS304
螺帽 Screw cap	SUS304
螺栓 Bolt	SUS304

性能规范 Specification

公称压力 Nominal Pressure	PN	1.6,2.5,4.0,6.4	MPa
强度试验压力 Strength testing pressure	PT	2.4,3.8,6.0,9.6	
低压气密封试验压力 Set testing pressure		0.6	
高压密封试验压力 Seat testing pressure		2.0,3.0,4.8,7.6	
适用介质 Applicable medium	Q11F-(16-64)C	Q11F-(16-64)P	Q11F-(16-64)R
	水、油品、气 Water, Oil, Steam	硝酸类 Nitric acid	醋酸类 Acetic acid
适用温度 Applicable Temperature		-40~180°C	

主要外形尺寸 Main outer size

单位 Unit mm

规格 Specification	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"
SIZE	6	10	15	20	25	32	40	50
L	65	44	55	60	72	77	88	100
D	11.6	7	9.2	12.5	16	20	24.5	32
H	44	36	41	44	48	54	65	72
w	100	73	86	86	103	103	140	140

